

SK 30 - DIN 2080



Weldonhouder DIN 6359
voor cilindrische schacht DIN 1835-B

SK30

Bestel nr.	Afmetingen
301.04.06	SK 40 - 06 - 40
301.04.08	SK 40 - 08 - 40
301.04.10	SK 40 - 10 - 40
301.04.12	SK 40 - 12 - 40
301.04.14	SK 40 - 14 - 40
301.04.16	SK 40 - 16 - 50
301.04.18	SK 40 - 18 - 50
301.04.20	SK 40 - 20 - 63



Morse Conus houder DIN 6383
voor MC met uitdrijflijp

SK30

Bestel nr.	Afmetingen
301.07.01	SK 30 - MC 1 - 50
301.07.02	SK 30 - MC 2 - 50
301.07.03	SK 30 - MC 3 - 75



Spantanghouder voor spantang
DIN 6499 type ER

SK 30

Bestel nr.	Afmetingen
301.02.16	SK 30 - 2 /16 -50 / ER 25
301.02.20	SK 30 - 2 /20 -50 / ER 32



Kombi-opsteekfreesdoorn
DIN 6358

SK 30

Bestel nr.	Afmetingen
301.10.16	SK 30 - 16 - 35
301.10.22	SK 30 - 22 - 35
301.10.27	SK 30 - 27 - 35
301.10.32	SK 30 - 32 - 50



Veiligheids sleutel ER

Bestel nr.	Afmetingen
02.16	sleutel ER 25
02.20	sleutel ER 32



Watermunt 178
NL - 5931 TL Tegelen
T +31 (0)77 3280124

info@technotool.nl
www.technotool.nl
M +31(0) 6 2002 4242

SK 30 - DIN 2080



Spantangen DIN 6499 ER

Rondloop 0,01 - 0,015 mm
geslepen en gehard



Spantang set in houten sokkel
Rondloop 0,01 - 0,015 mm
geslepen en gehard

Bestel nr.	Afmetingen
426 E - Ø (ER16)	1
426 E - Ø	2 - 10, 1 mm opl.
430 E - Ø (ER25)	2
430 E - Ø	3 - 16, 1 mm opl.
470 E - Ø (ER32)	2
470 E - Ø	3 - 20, 1 mm opl.
472 E - Ø (ER40)	3
472 E - Ø	4 - 26, 1 mm opl.

Bestel nr.	Afmetingen
426 E - S	426 E (ER 16; 10 st.) / 1 - 10
430 E - S	430 E (ER 25; 15 st.) / 2 - 16
470 E - S	470 E (ER 32; 18 st.) / 3 - 20
472 E - S	472 E (ER 40; 23 st.) / 4 - 26



Houten sokkel

Bestel nr.	Afmetingen
701.10.1	Gr. 10 (ER 16)
701.16.1	Gr. 16 (ER 25/OZ16)
701.20/25.1	Gr. 20 / 25 (ER32/OZ25)
701.26/32.1	Gr. 26 / 32 (ER40/OZ32)



Kantentaster mechanisch

Rondloop 0,005 mm

Bestel nr.	Afmetingen
702.10	10 - 84 -10
702.10.4	10 - 94 -10/4



ER spantanghouders met mini moer / cilindrische schacht
op aanvraag



Nulpunt insteller
zonder magneet
Referentiehoogte 50 mm

Bestel nr.	Afmetingen
702.5.48.1	68 - 50 - 48



Watermunt 178
NL - 5931 TL Tegelen
T +31 (0)77 3260124

info@technotool.nl
www.technotool.nl
M +31(0) 6 2002 4242

SK 40 - SK 50 - DIN 2080



Weldonhouder DIN 6359
voor cilindrische schacht DIN 1835-B

SK40

Bestel nr.	Afmetingen
401.04.06	SK 40 - 06 - 50
401.04.08	SK 40 - 08 - 50
401.04.10	SK 40 - 10 - 50
401.04.12	SK 40 - 12 - 50
401.04.14	SK 40 - 14 - 50
401.04.16	SK 40 - 16 - 63
401.04.18	SK 40 - 18 - 63
401.04.20	SK 40 - 20 - 63
401.04.25	SK 40 - 25 - 80
401.04.32	SK 40 - 32 - 80
401.04.40	SK 40 - 40 - 90



Weldonhouder DIN 6359
voor cilindrische schacht DIN 1835-B

SK50

Bestel nr.	Afmetingen
501.04.06	SK 50 - 06 - 63
501.04.08	SK 50 - 08 - 63
501.04.10	SK 50 - 10 - 63
501.04.12	SK 50 - 12 - 63
501.04.14	SK 50 - 14 - 63
501.04.16	SK 50 - 16 - 63
501.04.18	SK 50 - 18 - 63
501.04.20	SK 50 - 20 - 63
501.04.25	SK 50 - 25 - 80
501.04.32	SK 50 - 32 - 80
501.04.40	SK 50 - 40 - 90



Morse Conus houder DIN 6383
voor MC met uitdrijflijp

SK40

Bestel nr.	Afmetingen
401.07.01	SK 40 - MC 1 - 50
401.07.02	SK 40 - MC 2 - 50
401.07.03	SK 40 - MC 3 - 65
401.07.04	SK 40 - MC 4 - 95



Morse Conus houder DIN 6383
voor MC met uitdrijflijp

SK50

Bestel nr.	Afmetingen
501.07.01	SK 50 - MC 1 - 45
501.07.02	SK 50 - MC 2 - 60
501.07.03	SK 50 - MC 3 - 65
501.07.04	SK 50 - MC 4 - 70
501.07.05	SK 50 - MC 5 - 105



Morse Conus houder DIN 6364
voor MC met aantrekdraad

SK40

Bestel nr.	Afmetingen
401.08.01	SK 40 - MC 1 - 50
401.08.02	SK 40 - MC 2 - 50
401.08.03	SK 40 - MC 3 - 65
401.08.04	SK 40 - MC 4 - 95
401.08.04A*	SK 40 - MC 4 - 110



Morse Conus houder DIN 6364
voor MC met aantrekdraad

SK50

Bestel nr.	Afmetingen
501.08.01	SK 50 - MC 1 - 60
501.08.02	SK 50 - MC 2 - 60
501.08.03	SK 50 - MC 3 - 65
501.08.04	SK 50 - MC 4 - 65
501.08.04A*	SK 50 - MC 4 - 80
501.08.05	SK 50 - MC 5 - 120
501.08.05A*	SK 50 - MC 5 - 138
* Meenemervlak	volgens DIN 2201

SK40 - SK50 - DIN 2080



Meskop opsteekfreesdoorn
DIN 6357 met extra grote
kraag diameter

SK40

Bestel nr.	Afmetingen
401.11.16	SK 40 - 16 - 30
401.11.22	SK 40 - 22 - 30
401.11.27	SK 40 - 27 - 30
401.11.32	SK 40 - 32 - 30
401.11.40	SK 40 - 40 - 30



Meskop opsteekfreesdoorn
DIN 6357 met extra grote
kraag diameter

SK50

Bestel nr.	Afmetingen
501.11.22	SK 50 - 22 - 35
501.11.27	SK 50 - 27 - 35
501.11.32	SK 50 - 32 - 40
501.11.40	SK 50 - 40 - 33
501.11.60	SK 50 - 60 - 55



Kombi-opsteekfreesdoorn
DIN 6358

SK 40

Bestell Nr.	Abmessung
401.10.16	SK 40 - 16 - 52
401.10.22	SK 40 - 22 - 52
401.10.27	SK 40 - 27 - 52
401.10.32	SK 40 - 32 - 52
401.10.40	SK 40 - 40 - 52



Kombi-opsteekfreesdoorn
DIN 6358

SK 50

Bestel nr.	Afmetingen
501.10.16	SK 50 - 16 - 55
501.10.22	SK 50 - 22 - 55
501.10.27	SK 50 - 27 - 55
501.10.32	SK 50 - 32 - 55
501.10.40	SK 50 - 40 - 55



Spantanghouder voor spantang
DIN 6499 type ER

Bestel nr.	Afmetingen
401.02.16	SK 40 - 2 / 16 -50 / ER 25
401.02.20	SK 40 - 2 / 20 -50 / ER 32
401.02.26	SK 40 - 3 / 26 -80 / ER 40



Spantanghouder voor spantang
DIN 6499 type ER

Bestel nr.	Afmetingen
501.07.01	SK 50 - 2 / 20-63 / ER 32
501.07.02	SK 50 - 3 / 26-63 / ER 40



Veiligheids sleutel ER

Bestel nr.	Afmetingen
02.16	sleutel ER 25
02.20	sleutel ER 32
02.26	sleutel ER 40



Watermunt 178
NL - 5931 TL Tegelen
T +31 (0)77 3260124

info@technotool.nl
www.technotool.nl
M +31(0) 6 2002 4242

SK 40 - SK 50 - DIN 2080



Spantangen DIN 6499 ER

Rondloop 0,01 - 0,015 mm
geslepen en gehard



Spantang set in houten sokkel
Rondloop 0,01 - 0,015 mm
geslepen en gehard

Bestel nr.	Afmetingen
426 E - Ø (ER16)	1
426 E - Ø	2 - 10, 1 mm opl.
430 E - Ø (ER25)	2
430 E - Ø	3 - 16, 1 mm opl.
470 E - Ø (ER32)	2
470 E - Ø	3 - 20, 1 mm opl.
472 E - Ø (ER40)	3
472 E - Ø	4 - 26, 1 mm opl.

Bestel nr.	Afmetingen
426 E - S	426 E (ER 16; 10 st.) / 1 - 10
430 E - S	430 E (ER 25; 15 st.) / 2 - 16
470 E - S	470 E (ER 32; 18 st.) / 3 - 20
472 E - S	472 E (ER 40; 23 st.) / 4 - 26



Houten sokkel

Bestel nr.	Afmetingen
701.10.1	Gr. 10 (ER 16)
701.16.1	Gr. 16 (ER 25/OZ16)
701.20/25.1	Gr. 20 / 25 (ER32/OZ25)
701.26/32.1	Gr. 26 / 32 (ER40/OZ32)



Kantentaster mechanisch

Rondloop 0,005 mm

Bestel nr.	Afmetingen
702.10	10 - 84 - 10
702.10.4	10 - 94 - 10/4



ER spantanghouders met mini moer / cilindrische schacht
op aanvraag



Nulpunt insteller
zonder magneet
Referentiehoogte 50 mm

Bestel nr.	Afmetingen
702.5.48.1	68 - 50 - 48



Watermunt 178
NL - 5931 TL Tegelen
T +31 (0)77 3260124

info@technotool.nl
www.technotool.nl
M +31(0) 6 2002 4242