

ER SPANTANGEN - DIN 6499



Set ER spantangen in houten sokkel
Rondloop 0,01 - 0,015 mm

Bestel Nr.	Afmeting
4004 E - S	4004 E (ER 8 - 9 st.) / 1 - 5
4008 E - S	4008 E (ER 11-13 st.) / 1 - 7
426 E - S	426 E (ER 16 - 10 st.) / 1 - 10
428 E - S	428 E (ER 20 - 12 st.) / 2 - 13
430 E - S	430 E (ER 25 - 15 st.) / 1-16
470 E - S	470 E (ER 32 - 18 st.) / 2-20
472 E - S	472 E (ER 40 - 23 st.) / 4-26



Set ER spantangen in houten sokkel
Extra precisie , rondloop $\leq 0,005$ mm
gepolijst

Bestel Nr.	Afmeting
0426 E - S	0426 E (ER 16-10 st.) 1 - 10
0430 E - S	0430 E (ER 25-15 st.) 2 - 16
0470 E - S	0470 E (ER 32-18 st.) 3 - 20
0472 E - S	0472 E (ER 40-23 st.) 4 - 26



Spantangen DIN 6499 Systeem ER

Rondloop 0,01 - 0,015 mm
geslepen en gehard

Bestel Nr.	Afmeting
4004 E - Ø (ER 8)	1 - 1,5
4004 E - Ø	2 - 5 0,5 mm opl
4008 E - Ø (ER11)	1 - 1,5
4004 E - Ø	2 - 7 0,5 mm opl
426 E - Ø (ER16)	1 - 1,5 0,5 mm opl
426 E - Ø	2 - 10 1 mm opl.
428 E - Ø (ER20)	1 - 1,5 0,5 mm opl.
428 E - Ø	2 - 13 1 mm opl.
430 E - Ø (ER25)	2
430 E - Ø	3 - 16 1 mm opl.
470 E - Ø (ER32)	2
470 E - Ø	3 - 20 1 mm opl.
472 E - Ø (ER40)	3
472 E - Ø	4 - 26 1 mm opl.
577 E - Ø (ER50)	6-11 2 mm opl.
577 E - Ø	12-34 2 mm opl.



Spantangen DIN 6499 Systeem ER

Rondloop $\leq 0,005$ mm
geslepen, gehard en gepolijst

Bestel Nr.	Afmeting
0426 E - Ø (ER16)	1
0426 E - Ø	2 - 10, 1 mm opl.
0430 E - Ø (ER25)	2
0430 E - Ø	3 - 16, 1 mm opl..
0470 E - Ø (ER32)	2
0470 E - Ø	3 - 20, 1 mm opl.
0472 E - Ø (ER40)	3
0472 E - Ø	4 - 26, 1 mm opl.



Watermunt 178
NL - 5931 TL Tegelen
T +31 (0)77 3260124

info@technotool.nl
www.technotool.nl
M +31(0) 6 2002 4242