

HSK 63A - DIN 69893

G 2,5 / 25.000 omw./min.



Spantanghouder
voor spantangen DIN 6499 ER

Bestel Nr.	Afmetingen
A63.02.10.G2,5	HSK 63 - 1 / 10 - 75 ER16
A63.02.16.G2,5	HSK 63 - 2 / 16 - 75 ER25
A63.02.20.G2,5	HSK 63 - 2 / 20 - 75 ER32
A63.02.26.G2,5	HSK 63 - 3 / 26 - 90 ER40
A63.02.10.1.G2,5	HSK 63 - 1 / 10 - 100 ER16
A63.02.16.1.G2,5	HSK 63 - 2 / 16 - 100 ER25
A63.02.20.1.G2,5	HSK 63 - 2 / 20 - 100 ER32
A63.02.26.1.G2,5	HSK 63 - 3 / 26 - 120 ER40
A63.02.10.2.G2,5	HSK 63 - 1 / 10 - 160 ER16
A63.02.16.2.G2,5	HSK 63 - 2 / 16 - 160 ER25
A63.02.20.2.G2,5	HSK 63 - 2 / 20 - 160 ER32
A63.02.26.2.G2,5	HSK 63 - 3 / 26 - 160 ER40



Freeshouder DIN 6359 (weldon)
voor cilindrische schacht DIN 1835-B

Bestel Nr.	Afmetingen
A63.04.06.G2,5	HSK 63 - 06 - 65
A63.04.08.G2,5	HSK 63 - 08 - 65
A63.04.10.G2,5	HSK 63 - 10 - 65
A63.04.12.G2,5	HSK 63 - 12 - 80
A63.04.14.G2,5	HSK 63 - 14 - 80
A63.04.16.G2,5	HSK 63 - 16 - 80
A63.04.18.G2,5	HSK 63 - 18 - 80
A63.04.20.G2,5	HSK 63 - 20 - 80
A63.04.25.G2,5	HSK 63 - 25 - 110
A63.04.32.G2,5	HSK 63 - 32 - 110
A63.04.06.1.G2,5	HSK 63 - 06 - 120
A63.04.08.1.G2,5	HSK 63 - 08 - 120
A63.04.10.1.G2,5	HSK 63 - 10 - 120
A63.04.12.1.G2,5	HSK 63 - 12 - 120
A63.04.14.1.G2,5	HSK 63 - 14 - 120
A63.04.16.1.G2,5	HSK 63 - 16 - 120
A63.04.18.1.G2,5	HSK 63 - 18 - 120
A63.04.20.1.G2,5	HSK 63 - 20 - 120
A63.04.06.2.G2,5	HSK 63 - 06 - 160
A63.04.08.2.G2,5	HSK 63 - 08 - 160
A63.04.10.2.G2,5	HSK 63 - 10 - 160
A63.04.12.2.G2,5	HSK 63 - 12 - 160
A63.04.14.2.G2,5	HSK 63 - 14 - 160
A63.04.16.2.G2,5	HSK 63 - 16 - 160
A63.04.18.2.G2,5	HSK 63 - 18 - 160
A63.04.20.2.G2,5	HSK 63 - 20 - 160
A63.04.25.2.G2,5	HSK 63 - 25 - 160
A63.04.32.2.G2,5	HSK 63 - 32 - 160



Freeshouder DIN 6359 (weldon)
met koelkanaal voor cilindrische
schacht DIN 1835-B

Bestel Nr.	Afmetingen
A63.04.06.K.G2,5	HSK 63 - 06 - 65
A63.04.08.K.G2,5	HSK 63 - 08 - 65
A63.04.10.K.G2,5	HSK 63 - 10 - 65
A63.04.12.K.G2,5	HSK 63 - 12 - 80
A63.04.14.K.G2,5	HSK 63 - 14 - 80
A63.04.16.K.G2,5	HSK 63 - 16 - 80
A63.04.18.K.G2,5	HSK 63 - 18 - 80
A63.04.20.K.G2,5	HSK 63 - 20 - 80
A63.04.25.K.G2,5	HSK 63 - 25 - 110
A63.04.32.K.G2,5	HSK 63 - 32 - 110



Koelmiddel doorvoerunit

Bestel Nr.	Afmetingen
A63.700	HSK 63

HSK 63A - DIN 69893

G 2,5 / 25.000 omw./min.



Kombi-opsteekfreesdoorn
DIN 6358

Bestel Nr.	Afmetingen
A63.10.16.G2,5	HSK 63 - 16 - 60
A63.10.22.G2,5	HSK 63 - 22 - 60
A63.10.27.G2,5	HSK 63 - 27 - 60
A63.10.32.G2,5	HSK 63 - 32 - 60
A63.10.40.G2,5	HSK 63 - 40 - 70
A63.10.16.1.G2,5	HSK 63 - 16 - 100
A63.10.22.1.G2,5	HSK 63 - 22 - 100
A63.10.27.1.G2,5	HSK 63 - 27 - 100
A63.10.32.1.G2,5	HSK 63 - 32 - 100
A63.10.40.1.G2,5	HSK 63 - 40 - 100
A63.10.16.2.G2,5	HSK 63 - 16 - 160
A63.10.22.2.G2,5	HSK 63 - 22 - 160
A63.10.27.2.G2,5	HSK 63 - 27 - 160
A63.10.32.2.G2,5	HSK 63 - 32 - 160
A63.10.40.2.G2,5	HSK 63 - 40 - 160



Meskop freesdoorn
DIN 6357 met koelkanaal

Bestell Nr.	Afmetingen
A63.11.16.G2,5	HSK 63 - 16 - 50
A63.11.22.G2,5	HSK 63 - 22 - 50
A63.11.27.G2,5	HSK 63 - 27 - 50
A63.11.32.G2,5	HSK 63 - 32 - 60
A63.11.40.G2,5	HSK 63 - 40 - 60
A63.11.16.1.G2,5	HSK 63 - 16 - 100
A63.11.22.1.G2,5	HSK 63 - 22 - 100
A63.11.27.1.G2,5	HSK 63 - 27 - 100
A63.11.32.1.G2,5	HSK 63 - 32 - 100
A63.11.40.1.G2,5	HSK 63 - 40 - 100
A63.11.16.2.G2,5	HSK 63 - 16 - 160
A63.11.22.2.G2,5	HSK 63 - 22 - 160
A63.11.27.2.G2,5	HSK 63 - 27 - 160
A63.11.32.2.G2,5	HSK 63 - 32 - 160
A63.11.40.2.G2,5	HSK 63 - 40 - 160



Reduceerhuls voor Morse Conus
met uitdrijflip DIN 6383

Bestel Nr.	Afmetingen
A63.07.01.G2,5	HSK 63 - 1 - 100
A63.07.02.G2,5	HSK 63 - 2 - 120
A63.07.03.G2,5	HSK 63 - 3 - 140
A63.07.04.G2,5	HSK 63 - 4 - 160



CNC-Boorkop
rechts- en linksom inzetbaar

Bestel Nr.	Afmetingen
A63.15.16.G2,5	HSK 63 - 1,5 / 16 - 111



Watermunt 178
NL - 5931 TL Tegelen
T +31 (0)77 3260124

info@technotool.nl
www.technotool.nl
M +31(0) 6 2002 4242